

W332-Z00

AMD Ryzen™ Tower Entry Workstation



Features

- AMD Ryzen™ 7000 Processors
- 2-Channel ECC/Non-ECC DDR5 Unbuffered DIMM, 4 x DIMMs
- Realtek DASH Remote Management
- Realtek 2.5GbE LAN and 1GbE DASH LAN
- PCIe Gen5 Ready x16 slot and M.2 slot
- Rear HDMI / DP Support
- Up to 2x 3.5" HDD bays and 2x M.2 slots
- 500W 80 PLUS Bronze single power supply

Specification

Dimensions	Mini-Tower (W375 x H198 x D370 mm)	Peripheral Drives	ODD drive in option
CPU	AMD Ryzen™ 7000 Series Processors	Front I/O	2 x USB3.2 Gen1 ports, 1 x Line out port, 1 x Mic in port, 1 x Power Button, 1 x Hard drives status LED, 1 x Reset Button
Socket	Socket AM5	Rear I/O	1 x Display port, 1 x HDMI port, 3 x USB 3.2 Gen2 type A, 1 x USB 3.2 Gen2 type C, 1 x 2.5 GbE RJ45 LAN port, 1 x GbE RJ45 DASH LAN port, 3 x Audio Jacks, 2 x Antenna ports (reserved for option)
Chipset	AMD B550E	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
Memory	2-Channel DDR5 memory, 4 x DIMM slots Supported ECC Un-buffered DIMM 1Rx8/2Rx8 and non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Total up to 128GB of system memory (32GB single DIMM capacity) Memory speed: up to 5200MHz (1DPC) / 3600MHz (2DPC)	Power Supply	1 x 500W 80 PLUS Bronze power supply AC Input: 90-264V; 115V/ 7A, 230V/3A; 47-63Hz
LAN	2 x LAN ports - Realtek 2.5GbE LAN (RTL8125) - Realtek GbE DASH LAN (RTL8111EP)	System Management	Realtek DASH Remote Management
Video	1 x DP port: supporting maximum resolution of 4096x2160 @60Hz; Support for DP 1.2 version. 1 x HDMI port: supporting maximum resolution of 4096x2160 @60Hz; Support for HDMI 2.1 version, HDCP 2.3, HDR,	OS Compatibility	Windows 11 64-bit Windows 10 64-bit
Audio	Realtek ALC897 audio codec High Definition audio; 2/4/5.1/7.1-channel 3 ports Audio Jack (Line in/Line out/Mic) 2 x 3.5" fixed drive bays	System Fans	2 x 92x92x25mm (4500rpm)
Storage	2 x 3.5" fixed drive bays	Operating Properties	Operating temperature: 0°C to 35°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
RAID	RAID 0, 1, 10	Packaging Content	1 x W332-Z00 1 x Quick Start Guide
Expansion Slots	1 x PCIe x16 (Gen5 x16) slot; integrated from CPU 1 x PCIe x16 (Gen4 x4) slot; integrated from chipset 1 x PCIe x1 (Gen4 x1) slot; integrated from chipset 2 x M.2 slots for storage: - PCIe Gen5 x4; PCIe Gen4x4 - M-key; supports NGFF-2242/2280 1 x M.2 slot for Wi-Fi: - E-key; supports NGFF-2230	Reference Numbers	Barebone package: 6BW332Z00MR-00 - Chassis Kit: 25EC2-W33100-C1R - Motherboard: 9MC13NB0NR-00 - IO Shield: TBD - Power supply: 25EP0-20500B-F3S - System Fan: 25Y00-92250-A20R - SATA cable: 25CF4-350500-S9R



Learn more about GIGABYTE server solutions, visit www.gigabyte.com/Enterprise

* All specifications are subject to change without notice. Please visit our website for the latest information.

* AMD, and the AMD Arrow logo, AMD Ryzen and combinations thereof are trademarks of Advanced Micro Devices, Inc.

* All other brands, logos and names are property of their respective owners.

© 2022 GIGABYTE Technology Co., Ltd. All rights reserved.